
S9015LST1


General Purpose Transistors PNP

1. FEATURES

- The material of product compliance with RoHS requirements and Halogen Free.
- High Stability and High Reliability.
- Complementary to S9013(NPN)



SOT23 (TO-236)



2. Mechanical Data

- SOT-23 Small Outline Plastic Package.
- Tin plated leads, solderable per J-STD-002 and JESD22-B102.
- Marking: M6

3. ORDERING INFORMATION

Device	Min Pack	Inner Box	Outer Carton	Reel
S9015LST1	3000	45000	180000	7 inch

4. MAXIMUM RATINGS (Ta = 25°C)

Parameter	Symbol	Limit	Unit
Collector-Emitter Voltage	VCEO	-45	V
Collector-Base Voltage	VCBO	-50	V
Emitter-Base Voltage	VEBO	-5	V
Collector Current--Continuous	IC	-100	mA
Collector Power Dissipation	Pc	200	mW

5. THERMAL CHARACTERISTICS


Parameter	Symbol	Limit	Unit
Storage Temperature	TSTG	-55~150	°C
Junction Temperature	TJ	150	°C


6. ELECTRICAL CHARACTERISTICS (Ta= 25°C unless otherwise specified)


Parameter	Symbol	Condition	Min	Max	Unit
Collector–Emitter Breakdown Voltage	V(BR)CEO	IC = -0.1 mA, IB = 0	-45		V
Collector–Base Breakdown Voltage	V(BR)CBO	IC = -100μA, IE = 0	-50		V


Emitter–Base Breakdown Voltage	V(BR)EBO	IE = -100 μA, IC = 0	-5		V
Collector Cutoff Current	ICBO	VCB= -50 V, IE=0		-100	nA
Emitter cut-off current	IEBO	VEB= -5V, IC=0		-100	nA
DC current gain	hFE	IC = -1 mA, VCE = -5 V	200		450
Collector-Emitter Saturation Voltage	VCE(sat)	IC = -100 mA, IB = -10 mA		-0.3	V
Base–Emitter Saturation Voltage	VBE(sat)	IC = -100 mA, IB = -10 mA		-1	V
Transition frequency	fT	IC=-10mA, VCE= -5V, f = 30MHz	150		MHz


7. ELECTRICAL CHARACTERISTICS CURVES























8. OUTLINE AND DIMENSIONS








DIM	MIN	NOR	MAX
A	0.85	0.95	1.05
A1	0.01	0.06	0.10
b	0.36	0.44	0.52
c	0.09	0.13	0.18
D	2.80	2.90	3.10
E	1.20	1.30	1.40
e	1.78	1.90	2.04
L	0.30	0.40	0.50
L1	0.35	0.50	0.65
He	2.10	2.35	2.50
θ	0°	-	10°
All Dimensions in mm			

9. SUGGESTED PAD LAYOUT



SOT23		
DIM	mm	inch
A	2.00	0.079
B	0.95	0.037
C	0.95	0.037
X	0.80	0.031
Y	0.90	0.035

10. DISCLAIMER

The information presented in this document is for reference only. Sichuan Linkchip Technology Co., Ltd. reserves the right to make changes without notice to the specifications of the products displayed herein to improve reliability, functionality, or design.

When using any or all of the information contained in these materials, including product data, diagrams and charts, you are requested to carefully read this document and fully understand its contents. Sichuan Linkchip Technology Co., Ltd. assumes no responsibility for any damages, liabilities or losses resulting from the information contained herein.

All information contained in this document is current as of the issue date and subject to change without prior notice. For additional information, please visit our website or consult the nearest LCC's sales office for further assistance.